



CT4i

COMPACT AND VERSATILE

FEATURES

- /// Label and Wristband Printing
- /// High Speed Printing
- /// Printing Resolution of 203 / 305 / 609 dpi
- /// Anti-microbial Casing
- /// Small, Compact, High Throughput Design
- /// Easy Media Loading and Maintenance
- /// Wireless Connectivity
- /// RFID Ready

APPLICATIONS

- /// Healthcare
- /// General Office
- /// Government
- /// Library
- /// Retail
- /// Transportation and Logistics
- /// Entertainment

CT408i / CT412i / CT424i

PRINTING SPECIFICATION		CT408i	CT412i	CT424i
Printing Method		Direct Thermal, Thermal Transfer		
Print Resolution, dots/mm (dpi)		8dots/mm (203dpi)	12dots/mm (305dpi)	24dots/mm (609dpi)
Max. Print Area	Width, mm (inch)	104mm (4.1")		
	Length, mm (inch)	400mm (15.7")		
Print Speed, mm/sec (ips)		Up to 150mm/sec (6ips)	Up to 102mm/sec (4ips)	Up to 76mm/sec (3ips)
CPU		32 bit RISC		

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)				
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)		
Media Type		Roll or fan-fold die cut labels, Plain paper face stock, Linerless labels, Synthetics and Continuous stock		
Media Thickness		0.08 – 0.19mm (0.003” – 0.007”)		
Label Shape	Diameter		Max. outside diameter: Ø 110mm (4.33”), Core diameter: Ø 38.1mm (1.5”)	
	Wind Direction		Face-out	
Label Size	Continuous	Width	25 – 115mm (0.98” – 4.53”)	
		Length	15 – 397mm (0.59” – 15.6”)	
	Tear-Off	Width	25 – 115mm (0.98” – 4.53”)	
		Length	15 – 397mm (0.59” – 15.6”)	
	Cutter	Width	25 – 115mm (0.98” – 4.53”)	
		Length	15 – 397mm (0.59” – 15.6”)	
	Dispenser	Width	25 – 115mm (0.98” – 4.53”)	
		Length	15 – 397mm (0.59” – 15.6”)	
Ribbon	Size		Width: 45mm (1.77”) to 111mm (4.37”) Max. Length: 100m (328’)	
	Core Diameter		Ø 12.7mm (0.5”)	
	Wind Direction		Face-out	

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
	2D Barcode	
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

INTERFACE CHARACTERISTICS		
Standard Memory		Flash memory 4MB, SDRAM 16MB
Interface	Standard	Type 1: USB2.0 + RS232C; Type 2: USB2.0 + LAN
	Option (Type 1 only)	Wireless LAN 802.11b/g, Bluetooth, IEEE1284 Parallel

OPERATING CHARACTERISTICS		
Power Requirements		Input voltage AC100-240V (auto switching)/90W (peak) – Input voltage printer: 25V/2A
Dimensions		(W x D x H): 198 x 225 x 181mm (7.8" x 8.9" x 7.1")
Weight		3.0kg (6.6lbs) (excluding AC-Adapter)
Environment	Operating	5 – 35°C / 30 – 80% RH (without condensation)
	Storage	-5 – 60°C / 30 – 90% RH (without condensation)

MISCELLANEOUS	
Certifications	FCC, UL, CSA, CCC, CE, ROHS compliant
Regulatory	Noise: Emission – FCC, EN55022 Class B, Safety: CE, C-UL, TUV, CCC, MIC, HF: EN61000-3-2
Safety Standards	UL, CSA, CCC, CE, FCC Class B, MIC, TÜV, Printer complies to European Directive 2002/95/EC (RoHS)
Antibacterial Finishing	Resin of the enclosure / control panel includes an antibacterial substance. This substance is tested according to JISZ2801: Antimicrobial products - discourage the growth of bacteria and micro-organisms

OPTIONS	
Accessories	Cutter, Dispenser, Linerless, RFID HF 13,56 Mhz, Smart Keyboard, Unwinder, Rewinder, SATO Label Gallery™

RFID SPECIFICATION (optional)				
HF	Standard		ISO/IEC 15693	
	Frequency		13,56MHz	
	Transponder	NXP	I-code SLI	112 bytes
		TI	Tag-it HF-I	256 bytes
		Infineon	My-d	992 bytes
RFID Features			Fully integrated HF RFID Reader / Encoder Module, Void marking of damaged or unreadable transponders, RFID data verification after programming. UID reading and printing as text and barcode	



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.


Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service